

US009638295B2

(12) United States Patent

Rohs et al.

(10) Patent No.: US 9,638,295 B2 (45) Date of Patent: May 2, 2017

(54) FRICTION-RING TRANSMISSION HAVING TWO ROLLER BODIES SPACED APART FROM ONE ANOTHER BY A GAP

(71) Applicant: Ulrich Rohs, Dueren (DE)

(72) Inventors: Ulrich Rohs, Dueren (DE); Christoph

Draeger, Inden (DE); Werner Brandwitte, Langerwehe (DE)

(73) Assignee: Ulrich Rohs, Dueren (DE)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 541 days.

(21) Appl. No.: 14/091,721

(22) Filed: Nov. 27, 2013

(65) Prior Publication Data

US 2014/0087915 A1 Mar. 27, 2014

Related U.S. Application Data

(62) Division of application No. 11/922,375, filed as application No. PCT/DE2005/001391 on Aug. 5, 2005, now Pat. No. 9,316,293.

(30) Foreign Application Priority Data

Aug. 6, 2004	(DE)	10 2004 038 585
Aug. 6, 2004	(DE)	10 2004 038 586
Oct. 18, 2004	(DE)	10 2004 050 855

(51) **Int. Cl.** *F16H 15/42* (

(2006.01)

CPC *F16H 15/42* (2013.01) (58) Field of Classification Search

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

374,296	Α		12/1887	Evans
742,977	Α		11/1903	Evans
1,362,655	Α		12/1920	West
1,637,664	Α	*	8/1927	Stoeckicht F16H 15/42
				476/53
1,709,346	Α		4/1929	Garrard
2,239,983	A		4/1941	Bade
2,701,478	Α	*	2/1955	Riess B64C 25/20
				464/35
2,807,171	\mathbf{A}		9/1957	Wyckoff
(Continued)				

FOREIGN PATENT DOCUMENTS

CH	405 856 A	1/1966		
EP	0 878 641 A1	11/1988		
	(Continued)			

OTHER PUBLICATIONS

International Search Report of PCT/DE2005/001391, Mar. 15, 2006.

(Continued)

Primary Examiner — William C Joyce (74) Attorney, Agent, or Firm — Collard & Roe, P.C.

(57) ABSTRACT

A friction ring-type transmission includes two roller bodies which are arranged at a distance from each other about a gap, which correspond to each other via the friction ring and which rotate (5) on axial roller body axes. The friction ring is arranged in an adjusting bridge in such a manner that it can be axially displaced about an adjusting path along the gap and the adjusting bridge is mounted by an individual, axial guiding device.

13 Claims, 36 Drawing Sheets

